

# JMath

The template class JMath resides in the name space JMATH and constitutes an auxiliary *base* class. It implements the affirm + and negate - operators, the modifying arithmetic operators +=, -=, \*= and /= the non-modifying arithmetic operators +, -, \* and / of a derived class.

To make this work, a derived class A should provide for the corresponding policy methods.

```
class A :  
    public JMath<A>  
{  
public:  
    A& negate() { // implementation }  
    A& add(const A&) { // implementation }  
    A& sub(const A&) { // implementation }  
    A& add(const double) { // implementation }  
    A& div(const double) { // implementation }  
};
```

method	operators
	+X
negate()	-X
add(..)	+=, X + X
sub(..)	-=, X - X
mul(..)	*=x, x * X, X * x
div(..)	/=x, X / x

where X and x correspond to a value of type A and double, respectively. Note that it is not necessary to implement all methods. For example.

```
struct A :  
    public JMath<A>  
{  
    A() :  
        x(0.0),  
        y(0.0),  
        z(0.0)  
    {}  
  
    A(const double x,  
       const double y,  
       const double z) :  
        x(x),  
        y(y),  
        z(z)  
    {}  
  
    A& add(const A& object)  
    {  
        x += object.x;  
        y += object.y;  
        z += object.z;  
  
        return *this;  
    }
```

```

}

A& mul(const double factor)
{
    x *= factor;
    y *= factor;
    z *= factor;

    return *this;
}

friend inline std::ostream& operator<<(std::ostream& out, const A& object)
{
    using namespace std;

    out << FIXED(5,2) << object.x << ','
    << FIXED(5,2) << object.y << ','
    << FIXED(5,2) << object.z;

    return out;
}

double x;
double y;
double z;
};

```

The following

```

A a1( 1.0, 2.0, 3.0);
A a2(-1.0, -2.0, -3.0);

cout << +a1 << endl;
cout << a1 + a2 << endl;
cout << a1 * 2.0 << endl;
cout << 2.0 * a1 << endl;

a1 += a2;

cout << a1 << endl;

```

will produce

```

1.00 2.00 3.00
0.00 0.00 0.00
2.00 4.00 6.00
2.00 4.00 6.00
0.00 0.00 0.00

```